


# Marlow <sup>DATASHEET</sup>®

## DIABLO - STATIC ROPE FOR EXTREME USE

Marlow Diablo is a high quality, CE Type A certified rope with a special heat resistant cover. Designed for military, police and emergency services, Diablo is essential for all rope access professionals who require a low stretch kernmantle rope with added resistance to extreme environments and hard use.

When exposed to direct heat (for example from a blow torch or close proximity to halogen lamps), Diablo's survival time at temperatures exceeding 300°C, is 5 times that of regular static ropes. In instances of heat exposure up to 300°C, Diablo continues to maintain load bearing properties in excess of 10kN even after 15 minutes, whereas regular static ropes will catastrophically fail after 45 seconds.



### MATERIAL

<b>CORE:</b>	High tenacity Polyamide (Nylon)
<b>COVER:</b>	Blend of heat resistant para-aramid and high tenacity polyamide
<b>CORE TYPE:</b>	Multiple twisted cores
<b>COVER TYPE:</b>	24 plait braided
<b>CERTIFICATION:</b>	EN 1891 Type A

### CONSTRUCTION

#### CORES MANUFACTURED FROM HIGH TENACITY NYLON:

- Light weight
- High strength
- High energy absorption
- Good resistance to most chemicals and UV

#### PARA-ARAMID BLENDED COVER YARNS:

- Thick and durable cover for excellent abrasion resistance
- Excellent heat resistance, Para-aramid decomposes at over 500°C
- Thick para-aramid blended cover offers much improved insulation buffer zone between heat source and cores
- Improved cut resistance (by factor of 2) over standard ropes, thanks to the para-aramid element of the cover
- By blending the aramid with nylon the temperature of the rope is stabilised at approximately 220°C by the latent heat of fusion.
- Single cover is easily inspected for damage

#### TWISTED FIBRE COVER CONSTRUCTION:

- Excellent abrasion resistance
- Aids handling and works well with ascenders and descenders

#### SOLID BLACK OPTION:

Diablo is available in black for military and police applications.

#### HIGH VISIBILITY OPTION:

Diablo is available with high visibility fibre incorporated in the cover for emergency applications

**UV:** Performance of Diablo to EN 1891 is not adversely affected by exposure to UV.

## TERMINATIONS

### TERMINATION OPTIONS:

Marlow Diablo ropes can be terminated with a figure of eight knot or by sewn eyes. CE approved, factory sewn eyes using Marlow's computer controlled sewing machinery are available on request. Each eye is individually serial

## PERFORMANCE

PROPERTY	11MM (DIABLO)
Rope Classification Type (A or B)	A
Diameter (mm)	11
Sheath Slippage (%)	0
50 - 150 kg Elongation (%)	3.4
Shrinkage (%)	3.5
Mass Core (g/m)	38.4
Mass Cover (g/m)	44.1
Mass Rope (g/m)	82.5
Minimum Static Strength ex. terminations (kN)	22
Average Static Strength ex. terminations (kN)	35.5
Minimum Static Strength with terminations (kN)	15
Average Static Strength with sewn eye (kN)	29.2
Average Static Strength with fig. 8 loop (kN)	18.3
Peak Force (kN). Fig 8 loop	5.6
Fall Factor 1 falls. Fig. 8 loop	6

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

www.marlowropes.com  
UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com

### Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.

Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certification Number 315  
ISO 9001